



## IR-MARKER PROFESSIONAL

### TECHNICAL DATA VERSION V1

#### IR-MARKER

Dimensions	68 mm x 70 mm x 27 mm (2,68 in x 2,76 in x 1,06 in)
Operating temperature	0 - 40 °C
Weight	0,3 kg (incl. cable and mounting system)
Line voltage	7 - 20 V DC
Power consumption	2 W
Power connector	4 Pol / 2A Mini Plug
IR illumination	64 IR LEDs a 17mW/sr, 1 Khz Pulse
Fixation	different mounting plates (tripod mount, central plate, retaining plate)
Transport	Transport case

#### POWER DISTRIBUTION BOX

Input voltage	7-20 V
Operating temperature	0 - 40 °C
Weight	0,06 kg
Transport	Transport case

#### POWER SUPPLY

Input voltage	AC 100 V - 240 V with 50-60 Hz
Output voltage	DC 12 V
Power consumption	max. 10 W with 4 markers
Weight	0,4 kg

#### SCOPE OF DELIVERY IR-MARKER PROFESSIONAL

Up to 4 IR-Marker with cable	
Up to 4 adapter sets (assembly to different objects possible)	
1 x adapter box with power supply and 230 V cable	
1 x transport case	1,3 kg